# SAFETY DATA SHEET

## 1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: DESIGN MASTER TACK 1000 ADHESIVE Product Code: 1000

MARKETED BY: DESIGN MASTER color tool, inc.

ADDRESS: P.O. Box 601

Boulder, CO 80306 USA

EMERGENCY PHONE: 303-623-5716
INFORMATION PHONE: 800-525-2644
Product Use: Spray adhesive

## 2. HAZARDS IDENTIFICATION

## **CLASSIFICATION**

Flammable aerosol

Gas under pressure Liquefied gas

Acute Toxicity - Inhalation 4
Skin Corrosion/Irritation 3
Eye Damage/Irritation 2B



SIGNAL WORD: Danger

## **Hazard Statements**

Extremely flammable aerosol

Contains gas under pressure; may explode if heated

Causes mild skin irritation

Causes eye irritation

Harmful if inhaled

## **Precautionary Statements**

Keep away from heat/sparks/open flames/hot surfaces - No smoking

Do not spray on an open flame or other ignition source.

Pressurized container - Do not pierce or burn, even after use

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash hands thoroughly after handling

Use only outdoors or in a well-ventilated area

Call a POISON CENTER or doctor/physician if you feel unwell

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

If skin irritation occurs: Get medical advice/attention If eye irritation persists: Get medical advice/attention Protect from sunlight. Store in a well ventilated place

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

SDS for: 1000 Page 1 of 4

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Percent
ACETONE	67-64-1	20-30
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT	64742-49-0	15-20
PROPANE	74-98-6	10-15
BUTANE	106-97-8	10-15
CYCLOHEXANE	110-82-7	10-15
n-HEXANE	110-54-3	5-10

### 4. FIRST AID MEASURES

**INHALATION:** Remove to fresh air. Administer oxygen if needed. Apply artificial respiration if breathing has stopped. Get medical attention.

EYE CONTACT: Wash immediately with large volumes of fresh water for at least 15 minutes. Get medical attention.

SKIN CONTACT: Wipe off with a towel. Wash with soap and water. Get medical attention if irritation persists.

**INGESTION:** Not a likely route of exposure.

**Most important symptoms/effects, acute and delayed:** Repeated exposure may cause skin dryness or cracking. May cause drowsiness or dizziness.

Indication of immediate medical attention and special treatment needed: None known.

#### 5. FIRE FIGHTING MEASURES

**Suitable and unsuitable extinguishing media:** Foam, Alcohol foam, CO2, Dry chemical, Water fog. Water spray may be ineffective.

**Specific hazards arising from the chemical:** Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents. Liquid content of container will support combustion. Overexposure to decomposition products may cause a health hazard. Symptoms may not be readily apparent. Obtain medical attention. Hazardous decomposition products include carbon dioxide, carbon monoxide, and other toxic fumes

**Special equipment and precautions for fire-fighters:** Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat. Wear goggles and use self-contained breathing apparatus. If water is used, fog nozzles are preferred.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions, protective equipment, and emergency procedures:** Avoid breathing vapors. Ventilate area. Remove all sources of ignition.

**Methods and materials for containment and cleaning up:** Clean up with absorbent material and place in closed containers for disposal.

## 7. HANDLING AND STORAGE

**Precautions for safe handling:** Do not puncture or incinerate (burn) cans. Do not stick pins, nails, or any other sharp objects into opening on top of can. Do not spray in eyes. Do not take internally. See product label for additional information.

SDS for: 1000 Page 2 of 4

**Conditions for safe storage, including any incompatibilities:** Store and use in cool, dry, well-ventilated areas. Do not store above 120 F.

## 8. EXPOSURE CONTROL/PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
ACETONE 67-64-1	PEL-TWA: 750 ppm	TLV-TWA 500 ppm TLV-STEL 750 ppm	
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT 64742-49-0	TWA: 500 ppm; PEL-CEILING: not determined	TLV-TWA: 400 ppm TLV-STEL: 500 ppm	
PROPANE 74-98-6	Not established	TWA: 1000 ppm	
BUTANE 106-97-8	Not established	TWA: 1000 ppm	
CYCLOHEXANE 110-82-7	PEL: 300 ppm	TWA: 100 ppm	NIOSH: 300 ppm
n-HEXANE 110-54-3	PEL-TWA: 500 ppm PEL-CEILING: Not determined	TLV-TWA: 50 ppm; TLV-STEL: Not determined	

**Appropriate engineering controls:** Ventilation should be sufficient to prevent inhalation of any vapors. General dilution and/or local exhaust ventilation in volume to keep PEL/TLV of most hazardous ingredient below acceptable limit and lel below stated limit.

#### Individual protection measures:

**Respiratory protection:** None under normal use. Avoid breathing vapors. In restricted areas, use approved chemical/mechanical filters designed to remove a combination or particles and vapor. In confined areas, use an approved air line respirator or hood. Self-contained breathing apparatus is required for vapor concentrations above PEL/TLV limits.

Protective gloves: None under normal use. Use solvent-resistant for prolonged or repeated contact.

**Eye protection:** None under normal use. However, use of safety glasses with splash guards or full face shield should be used if indicated.

**Other protective clothing or equipment:** None under normal use. However, use of solvent- resistant aprons or other clothing is recommended. Eye washes and safety showers in the workplace are recommended.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Freezing point: Not dete	rmined Solubility: Not determined
Boiling point: Not dete	rmined Flash point: Not determined
Evaporation rate: Slower th	nan ether Flammability: Level 3 Aerosol
Explosive Limits: Not appl	icable Partition coefficient (n- Not determined octanol/water):
Autoignition temperature: Not dete	rmined Decomposition temperature: Not determined
Viscosity: Not dete	rmined Appearance: Aerosol product
Odor: Solvent	Vapor Pressure: Not determined
Odor threshold: Not dete	rmined Vapor Density: Heavier than air
pH: Not appl	icable Density: Not applicable
Melting point: Not dete	rmined

SDS for: 1000 Page 3 of 4

#### 10. STABILITY AND REACTIVITY

Reactivity: Not reactive under normal conditions of use.

Chemical stability: Stable under normal storage and handling conditions.

Possibility of hazardous reactions: None known.

#### Incompatible materials:

Acids, Bases, Strong oxidizing agents

Hazardous decomposition products:

Carbon dioxide, carbon monoxide, smoke, fumes, and other products of incomplete combustion.

#### 11. TOXICOLOGICAL INFORMATION

Long-term toxicological studies have not been conducted for this product.

#### 12. ECOLOGICAL INFORMATION

Long-term ecological studies have not been conducted for this product.

#### 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with local, state, and federal regulations. Before attempting clean up, refer to other sections of this document for hazard cautionary information.

#### 14. TRANSPORT INFORMATION

By land: DOT Proper Shipping Name: None required per 49 CFR 173.306(i) for products that conform to the Limited Quantity provisions. Commodity shipping description: Adhesive, NOI

By water: DOT & IMDG Proper Shipping Name: UN1950, Aerosols, 2.1, LTD QTY

By air: DOT & IATA Proper Shipping Name: UN1950, Aerosols, flammable, 2.1, LTD QTY (packing instruction Y203 applies)

## 15. REGULATORY INFORMATION

All ingredients are either listed on the TSCA inventory or are exempt.

## 16. OTHER INFORMATION

Date revised: 2015-09-24 Revision 0

Date Printed: 2015-09-25

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. BECAUSE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL, WE ASSUME NO RESPONSIBILITY FOR ITS USE.

SDS for: 1000 Page 4 of 4